



## PACER R35 BLADE PUTTY

### Description

Pacer R35 Blade Putty is a ready-to-use, ultra-fine nitro-cellulose finishing putty designed for filling scratches, pin-holes, sanding marks and minor surface imperfections in automotive and industrial applications. It offers excellent adhesion to properly prepared substrates, fast drying and smooth sanding.

### Surface Preparation

Surfaces must be clean, dry and free from contaminants. Surface should be abraded with 220–320 grit. For deeper scratches or previous filler repairs, 180 grit may be used, followed by refinement to 240–320 grit and wipe with Pacer Wax & Grease Remover.

### Application

Apply a thin, even layer using a flexible spreader. Work into imperfections and feather edges. Apply additional coats as required. Recommended application temperature: 15°C–35°C.

### Drying and Sanding

20°C: 20 minutes | 40°C: 15 minutes | 60°C: 8 minutes

Drying times vary with film build and conditions. Sand with 240–400 grit before priming or top coating.

### Technical Data

Raw Material Base: Nitrocellulose blends

Colour: Yellow

VOC Content: 550 g/L (34.3%)

Texture: Ultra fine knifing putty

Pack Size: 375 g

### Compatibility

Suitable under acrylic and nitrocellulose systems. Seal with a primer-surfacer before applying 2K topcoats.

### Storage and Shelf Life

Store sealed in a cool, dry place away from sunlight and ignition sources. Shelf life: 12 months unopened.

### Clean Up

Clean tools with lacquer thinner or automotive solvent.

### Health & Safety

Highly flammable. Use in well-ventilated areas. Avoid inhalation of fumes and sanding dust. Wear appropriate PPE. Refer to SDS.

### Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and are to the best of our knowledge true and accurate. The user must ensure suitability of the product for their specific application. Liability is restricted to replacement of faulty material. CW Brands reserves the right to change specifications at any time. Ensure current literature is used. No warranty is expressed or implied.